

LANCASTER

T I R E S



PRODUCT CATALOG



LR-66



LP-16



LX-01



LS-07 H/T



LS-37 A/T



LS-57 R/T



LS-67 M/T



The **LR-66** ultra-high-performance all-season tire is specially designed for the driving enthusiast; delivering responsive handling, cornering stability, and traction.

SIZE	SERV	SIZE	SERV	SIZE	SERV	SIZE	SERV
195/55R16 SL	87V	215/55ZR17 XL	98W	235/40ZR18 XL	95W	225/35ZR20 XL	93W
205/45ZR16 XL	87W	225/45ZR17 XL	94W	235/45ZR18 XL	98W	235/35ZR20 XL	92W
205/50ZR16 SL	87W	225/50ZR17 XL	98W	235/50ZR18 XL	101W	245/35ZR20 XL	95W
205/55R16 SL	91V	225/55ZR17 XL	101W	245/40ZR18 XL	97W	245/40ZR20 XL	99W
205/60R16 SL	92V	235/45ZR17 XL	97W	245/45ZR18 XL	100W	245/45ZR20 XL	103W
205/65R16 SL	95H	235/50ZR17 XL	100W	255/35ZR18 XL	94W	255/35ZR20 XL	97W
215/55ZR16 XL	97W	235/55ZR17 XL	103W	225/40ZR19 XL	93W	275/30ZR20 XL	97W
215/60R16 SL	95H	245/40ZR17 XL	95W	235/35ZR19 XL	91W	275/40ZR20 XL	106W
225/50ZR16 SL	92W	245/45ZR17 XL	99W	235/40ZR19 XL	96W	275/45ZR20 XL	110V
225/55ZR16 XL	99W	215/40ZR18 XL	89W	225/30ZR20 XL	85W	285/50R20 SL	112V
225/60R16 SL	98V	225/40ZR18 XL	92W				
235/60R16 SL	100H	225/45ZR18 XL	95W				
205/40ZR17 XL	84W						
205/45ZR17 XL	88W						
205/50ZR17 XL	93W						
215/45ZR17 XL	91W						
215/50ZR17 XL	95W						



The **LP-16** all-season touring tire is engineered for small to midsize vehicles offering drivers a quiet and comfortable ride with excellent handling.

- Optimized pitch sequence reduces tread pattern noise for a quiet ride.
- Wide circumferential grooves and siping improves traction in wet and light snow conditions.

SIZE	SERV
175/65R15 SL	84H
185/55R15 SL	82V
185/60R15 XL	88H
185/65R15 SL	88H
195/50R15 SL	82V
195/55R15 SL	85V
195/60R15 SL	88V
195/65R15 SL	91V
205/60R15 SL	91V
205/65R15 SL	94H
215/65R15 XL	100H
205/70R15 SL	96H
215/70R15 SL	98T



The **LX-01** sport truck tire is designed with an asymmetric tread pattern to provide exceptional handling and stability for the larger fitment sizes.

- Optimized pitch sequence reduces tread pattern noise for a quiet ride.
- Large shoulder elements provide tire stability and enhanced control when cornering.

SIZE	SERV
265/50R20 XL	111V
235/30ZR22 XL	90W
245/30ZR22 XL	92W
255/30ZR22 XL	95Y
265/35R22 XL	102V
265/40R22 XL	106V
305/40R22 XL	114V
305/45R22 XL	118V
255/30ZR24 XL	97W
275/25ZR24 XL	96W
275/30ZR24 XL	101W
305/35R24 XL	112V
305/30ZR26 XL	109W



The **LS-07 H/T** crossover and sport utility all-season tire is engineered for small to midsize vehicles offering drivers a quiet and comfortable ride with excellent handling.

- Optimized pitch sequence reduces tread pattern noise for a quiet ride.
- Wide circumferential grooves and siping improves traction in wet and light snow conditions.

SIZE	SERV	SIZE	SERV
235/75R15 XL	109T	245/65R17 SL	107H
215/65R16 SL	98H	245/70R17 SL	110H
215/70R16 SL	100H	265/70R17 SL	115T
225/70R16 SL	103T	235/55R18 XL	104V
235/65R16 XL	107H	235/60R18 XL	107V
235/70R16 SL	106T	255/55R18 XL	109W
245/70R16 XL	111T	265/60R18 SL	110H
255/70R16 SL	111H	275/65R18 SL	116H
265/70R16 SL	112T	275/55R20 XL	117H
215/60R17 SL	96V	275/60R20 SL	115T
225/60R17 SL	99V		
225/65R17 SL	102T		
235/60R17 SL	102H		
235/65R17 XL	108H		



The **LS-37 A/T** is a purpose build tire designed for off-road terrains with excellent on-road manners available in both sport utility and light truck sizes.

- The specially designed tread pattern delivers excellent on-road and off-road all-terrain performance.
- The zig-zag grooves provide added traction in mud, dirt, and other soft surface terrains.

SIZE	SERV	SIZE	SERV
235/70R16 SL	106T	LT225/75R16	115/112S
265/70R16 SL	112T	LT245/75R17	121/118S
275/70R16 SL	114S	LT285/70R17	121/118Q
265/65R17 SL	112S	LT275/65R18	123/120S
275/65R17 SL	115S	LT275/70R18	125/122S
285/65R17 SL	116S		
255/50R18 XL	106H		
265/40R18 XL	101H		
275/55R20 XL	117H		
285/45R22 XL	114H		



The **LS-57 R/T** is engineered to conquer the rugged off-road adventures and bring you home with excellent on-road handling.

- The specially designed multi-angle tread blocks provide excellent off-road performance in mud, dirt, gravel, and other soft surfaces.
- Integrated stone ejector ribs protect the carcass from stone drilling.

SIZE	SERV
LT285/55R20	122/119Q
33x12.50R17LT	120Q
35x12.50R17LT	121Q
33x12.50R18LT	118Q
35x12.50R18LT	123Q
33x12.50R20LT	114Q
35x12.50R20LT	121Q
33x12.50R22LT	109Q
35x12.50R22LT	117Q



The **LS-67 M/T** is made for consumers seeking the ultimate in off-road traction; whether it be mud, dirt, sand, gravel or rocks.

- The highly aggressive dual (A/B) pitch pattern provides excellent off-road performance in mud, dirt, gravel, and other soft surfaces.
- Integrated stone ejector ribs protect the carcass from stone drilling.

SIZE	SERV	SIZE	SERV
LT285/70R17	121/118Q	35X12.50R22LT	121Q
LT285/55R20	122/119Q	37X13.50R22LT	128Q
33X12.50R15LT	108Q	35x12.50R24LT	111Q
35X12.50R15LT	113Q	37x13.50R24LT	124Q
33x12.50R17LT	120Q		
35x12.50R17LT	121Q		
33x12.50R18LT	118Q		
35x12.50R18LT	123Q		
33X12.50R20LT	114Q		
35X12.50R20LT	121Q		
37X13.50R20LT	128Q		
33X12.50R22LT	114Q		



[illegible]

Lancaster Tires (LPP) Limited Protection Policy

Thank you for your interest in Lancaster brand tires for your vehicle. We are proud of the quality and performance of the wide range of Lancaster products, and we understand that your continued satisfaction is essential to our success.

Eligibility

This Limited Protection Policy applies to Lancaster brand passenger and light truck tires purchased on or after June 1, 2022, or, in the absence of proof of purchase, tires with a manufacturing DOT code reading DOT 2022 or later. Eligible tires are covered by this Limited Protection Policy for up to 60 months from the date of purchase or tire manufacturer date. This Limited Protection Policy applies to the original owner of new Lancaster branded passenger and light truck tires that are operated in normal service and used on the same vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. Only Lancaster tires purchased and operated in the United States and Canada are covered by this Limited Protection Policy. For Lancaster branded product purchased thru an online retailer, a tire claim must go back to the original selling Lancaster dealer. The online retailer where the Lancaster branded product was purchased would need to facilitate the claim with that authorized Lancaster dealer on the consumer's behalf.

What is covered by our exclusive No Questions Asked, 25/365 Free Replacement Limited Protection Policy?

The Lancaster No Questions Asked, 25/365 Free Replacement Limited Protection Policy will fully cover (100% credit) all eligible Lancaster brand passenger and light truck tires should one become unserviceable due to defective workmanship, materials, road hazard or a condition other than those listed below during the first 25% of usable treadwear or one year from date of purchase, whichever occurs first.

Tires not eligible for the No Questions Asked, 25/365 Free Replacement Limited Protection Policy that are removed from service due to a covered condition will be replaced with a comparable new Lancaster brand tire on a prorated basis for a period up to 60 months from the date of purchase or tire manufacturer date, or when the treadwear indicators become visible (worn to 2/32"), whichever occurs first.

What is a comparable tire?

A comparable tire may be either the same line and pattern of tire or, in the event that the tire is not available, a tire of the same construction and quality with a different sidewall or tread configuration. If a higher priced tire is accepted as replacement, the difference in price will be at an additional charge to the owner. Any Lancaster brand replacement tire provided pursuant to this Limited Protection Policy will be covered by the Lancaster Limited Protection Policy in effect at the time of replacement.

Mileage coverage plan

If an eligible tire wears down to the treadwear indicator bars (2/32") and the tire has not delivered the miles specified below, Lancaster will provide a prorated adjustment based on actual mileage delivered. The cost of mounting, balancing and any other service charges including applicable taxes are excluded from reimbursement.

Pattern	Coverage Plan (Miles/Km)	25/365	Workmanship & Materials (Mo.)
LX-01	40,000/65,000	Yes	60
LR-66	45,000/75,000	Yes	60
LP-16	60,000/100,000	Yes	60
LS-37 A/T	45,000/75,000	Yes	60
LS-07 H/T	60,000/100,000	Yes	60
LS-67 M/T	N/A	Yes	60
LS-57 R/T	40,000/65,000	Yes	60

The Mileage Coverage Plan applies only to the original purchaser and the tires have been used only on the vehicle on which they were originally installed according to the vehicle manufacturer's recommendations. The Mileage Coverage Plan does not apply to tires used in commercial applications. Tires that have not been rotated at least every 6,000 miles as evidenced by a completed rotation schedule are excluded. Likewise, tires in service for more than 60 months regardless of mileage attained are excluded.

What is not covered by the Limited Protection Policy?

- Improper operation or maintenance. This includes, but is not limited to, effects caused by improper tire inflation and/or improper load/speed practices and/or improper or insufficient tire rotation.
- Wear due to improper vehicle alignment including but not limited to, uneven, cupping, irregular, spotty and feathering wear
- Deliberate abuse or vandalism
- Ride or vibration complaint after the first 1/32" of treadwear
- Damage due to snow chain usage, improper mounting/dismounting or automotive accident
- Tires used in a commercial applications are not eligible for 25/365 or Mileage coverage where applicable.

Owner's obligations

To make an eligible claim under this Limited Protection Policy, tires must be rotated with the prescribed rotation patterns as recommended by either the vehicle owner's manual or an authorized Lancaster tire dealer. Owner must present an original tire sales invoice indicating the date of purchase, tire description and odometer mileage. Adjustment tires must be presented to an authorized Lancaster dealer and those tires replaced become the property of Lancaster Tires. Installation charges such as mounting, dismounting and balancing, as well as, any applicable taxes and government-mandated charges on the services rendered at the time of adjustment is the owner's responsibility. Adjustment claims must be completed on an approved claim form, supplied by an authorized Lancaster dealer, and submitted at time of adjustment.

What are your legal rights?

No Representative or Dealer has authority to make any representation, promise or agreement on behalf of Lancaster, except as stated herein.

Any tire, no matter how well constructed, may fail in service or otherwise become unserviceable due to conditions beyond the control of the tire manufacturer. Under no circumstances is this Limited Protection Policy a representation that a tire failure cannot occur. This Limited Protection Policy gives you specific legal rights and you may also have other rights that vary from state to state or province to province.

Disclaimer: This Limited Protection Policy is in lieu of, and Lancaster Tires hereby disclaims, any and all other Limited Protection Policies and representations, express or implied, including without limitation any Protection Policy of merchantability of fitness for a particular purpose, and no other Limited Protection Policy or representation of any kind is made by Lancaster Tires or shall be implied by law. This Limited Protection Policy is subject to change without notice.

Limitation of damages: In no event and under no circumstance shall Lancaster Tires be liable to the buyer for any indirect, special, incidental, consequential, lost profit, loss of business, loss of goodwill or reputation, punitive or other damage, cost (including for replacement transportation), expense or loss of any kind. Some states and provinces do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.

Lancaster tire care and maintenance guide

Proper inflation pressure is essential for optimum tire performance, safety, and fuel economy. Check for proper inflation pressure at least monthly while tires are cool, as tires will warm up from use after several miles so it is best to check before driving. Use a quality handheld accurate air pressure gauge. It is best to occasionally have your Lancaster tires inspected by a professional tire shop, as it is difficult to tell just by looking at radial tires whether they are under-inflated or over-inflated. Furthermore, when operating a vehicle equipped with radial tires, it is difficult to notice when a tire has gone flat or nearly flat since the handling of the vehicle may not deteriorate significantly. Remember to always maintain inflation pressure at the level recommended by the vehicle manufacturer as shown on the vehicle placard, on the vehicle certification label or in the vehicle owner's manual.

Evidence of air loss or repeated under-inflation always requires expert inspection to determine the source of leakage and tire removal to determine repairability. To avoid injury, NEVER attempt to re-inflate a tire that has been in operation severely under-inflated. Progressive air loss may result from a variety of conditions such as punctures, cuts, curbing, impacts or partial bead unsealing. Some installation or fitment causes for air loss are (1) incomplete bead seating, (2) tearing of the tire bead caused by a machine tool due to insufficient lubrication or improper adjustment, and (3) leaking valve core or rubber valve components. These should be corrected or replaced when problems are detected and/or whenever tires are replaced.

Under-inflation is the leading cause of tire failure and may result in severe cracking, component separation or complete loss of air. Under-inflation reduces tire load carrying capacity, allows for excessive sidewall flexing and increases rolling resistance, resulting in potential heat build-up and mechanical damage. Maintaining proper inflation pressure is the most important thing you can do to help promote tire safety, durability and maximize tread life.

Over-inflation will deteriorate ride quality, reduce braking ability and generate unwanted vibration. Over-inflation also increases the chances of impact damage.

Don't overload your vehicle

The maximum load capacity stamped on the sidewalls of P-metric tires is reduced by ten percent when used on a light truck, utility vehicle. Never fit P-metric tires to light trucks that specify LT-type replacement tires.

